



Australasian Explosives Industry Safety Group Inc.

## **Code of Practice**

# **BLAST GUARDING IN AN OPEN CUT MINING ENVIRONMENT**

**Edition 2  
November 2018**



Australasian Explosives Industry Safety Group Inc.

## **CODE OF PRACTICE**

# **BLAST GUARDING IN AN OPEN CUT MINING ENVIRONMENT**

**Edition 2**

**November 2018**



## About the AEISG

The Australian Explosives Industry Safety Group (AEISG) is an incorporated association of Australian explosives manufacturers and suppliers originally formed in 1994.

Since then, AEISG membership has grown substantially to include most of the Australasian explosives industry. A full list of all current member organisations can be found on the AEISG website, [www.aeiscg.org.au](http://www.aeiscg.org.au)

The goal of AEISG is to continuously improve the level of safety and security throughout our industry in the manufacture, transport, storage, handling and use of explosives and related materials across the region.

One of the strategies adopted by AEISG in this regard is to identify areas where improved and consistent standards of operational safety and security need to be applied, and then develop appropriate codes which reflect industry best practice in these areas.

AEISG codes of practice are adopted by members for the benefit of their employees, their customers and the general community. In the interest of promoting safety and security, the codes are freely available on the AEISG website.

To keep abreast of technological advancements, industry progress and regulatory changes, AEISG Codes of Practice are subject to regular review and updated through the issue of amendments or revised editions as necessary. It is important that users ensure they are in possession of the latest edition and aware of any amendments. References to superseded versions should be updated accordingly.

The goal of the AEISG is to continuously improve the level of safety throughout our industry in the manufacture, transport, storage, handling and use of, precursors and explosives in commercial blasting throughout Australia.

## Copyright

© AEISG Inc. 2018

This document is subject to copyright. No parts of it should be reproduced without the written consent of copyright owner.

**ISBN 978-1-921308-23-9**

## Disclaimer

AEISG Inc has taken reasonable care in the preparation of the information contained in this Code and believes it to be accurate. However, AEISG Inc does not guarantee or warrant the accuracy, completeness or currency of the information contained in this Code. As AEISG Inc cannot anticipate or control the conditions under which this information may be used, each user should review the information in the specific context of the intended application. Under no circumstances will AEISG Inc or any of its members be responsible for, or accept liability for, any loss, expense, cost or damage of any nature resulting from the use of or reliance upon the information contained in this Code. To the fullest extent permitted by law, AEISG Inc disclaims all warranties, whether express, implied, statutory or otherwise, in relation to the information contained in this Code.



## Contents

<b>Preamble</b> .....	5
<b>1.0 Scope</b> .....	5
<b>2.0 Definitions</b> .....	6
<b>3.0 General Requirements</b> .....	9
<b>3.1 PPE and Special Equipment for the Task</b> .....	9
<b>3.2 Selection of Personnel to be a Blast Guard or Sweeper</b> .....	10
<b>3.3 Required Competencies and Training</b> .....	10
<b>3.4 Records</b> .....	11
<b>4.0 Risk Assessment</b> .....	12
<b>5.0 Blasting Notification</b> .....	13
<b>6.0 Public Roadway/Railway Closures/Air Traffic</b> .....	16
<b>7.0 The Blast Guard Process</b> .....	17
<b>8.0 Pre-Blast Meeting</b> .....	20
<b>9.0 Establishing the Blast Guard Positions</b> .....	22
<b>9.1 Blast Guarding during a Thunder Storm</b> .....	23
<b>9.2 Blast Guarding during an Emergency</b> .....	23
<b>10.0 Clearing the Blast Exclusion Zone</b> .....	24
<b>11.0 Firing the Shot</b> .....	26
<b>11.1 The Management of Post-Blast Fume</b> .....	26
<b>12.0 Blast Fired</b> .....	29
<b>13.0 Misfire Management</b> .....	331
<b>Appendix A</b> .....	331
<b>Appendix B</b> .....	332
<b>Appendix C</b> .....	333



## PREAMBLE

The use of explosives to break rock is an intrinsically hazardous process. On a mine or quarry site the potential hazards are increased by the need to manage the blasting procedure to protect mine personnel, contractors and the general public from exposure to foreseeable, if unintended, adverse consequences of a blast.

Adverse consequences may include, but not be limited to, one or any combination of the following scenarios:

- Persons inadvertently at risk from flying rock generated by the blast
- Persons at risk from fumes/dust generated by the blast
- Persons at risk from misfired blastholes
- Persons carrying out tasks other than blasting with workplaces inside an area subject to blasting effects
- Electrical storms arriving when a blast is ready to fire
- Unauthorized persons unintentionally driving or walking inside a blasting zone
- Blast effects extending outside the mine boundaries

This Code has been developed to provide practical guidance on meeting regulatory requirements on mine safety. In the event of any conflict between this Code and regulatory requirements the regulations shall always take precedence.

The information is provided in good faith and without warranty.

## 1.0 SCOPE

- 1.1 This Code sets out the recommendations and precautions to protect the community, customers, employees and the environment in relation to the duties and obligations of persons performing all of the roles associated with the process 'Blast Guarding' in an open cut mining environment.
- 1.2 This code does not cover the guarding of explosives against unauthorised access once loading has commenced.



## 2.0 DEFINITIONS

Definitions used within this Code where applicable are consistent with the meanings as defined in AS2187.0

**Associated works** - Other magazines, process buildings and storages of energetic materials, e.g. ammonium nitrate or Class 5 dangerous goods.

**Blast Boards** – Designated boards located in areas where general mining personnel gather or pass, dedicated to the site blasting activities and indicating the location, time and date of any scheduled blasting on a mine site. The site Blast Boards will be updated at least the day before the shift start on the day of firing.

**Blast Controller** – A person who should be appointed to handle the logistics of the clearance of the Blast Exclusion Zone including (but not limited to) the following: -

- Establishing the personnel and equipment exclusion zones.
- Removal/relocation and preparation of equipment currently within the Blast Exclusion Zone;
- Confirming the locations of the Blast Guards and the Shotfirer;
- Confirming the clearance Sweepers of the Blast Exclusion Zone once the guards are in place and the area secured.
- Establishing the Fume exclusion zone
- Hold a pre-blast meeting ensuring all personnel involved in the blast, Blast Guards, Sweepers, Shotfirers are aware of their roles, responsibilities, hazards and controls.

Note: - The role of Blast Controller should not be performed by the Shotfirer in conjunction with their other role in the handling and firing of the explosives but by another suitably qualified person such as an Open Cut Examiner (in a coal mining environment) or Blasting Supervisor.

The extent of the responsibilities of the Blast Controller may be dictated by the degree of activities associated with any individual blast.

**Blast Exclusion Zone** – The area that is determined by the risk assessment process, to ensure that all the potential/foreseen hazards and effects of the blast, are controlled within the designated area. The Blast Exclusion Zone should be layered, with defined minimum distances firstly for equipment a secondly for personnel and a thirdly for NOx Fume.

**Blast Guard** -Industry terminology for a hard barrier consisting of a suitable person and equipment (visual indicators, suitable vehicle and communications equipment), strategically located to act as a hard barrier against unauthorised access to a designated Blast Exclusion Zone.



**Post-Blast Fume** – The cloud of material generated after the initiation of ammonium nitrate-based explosives which is sometimes yellowish through to a red / brown colour. The cloud will generally be composed of the following materials:

- Dust and other soil / rock particulate matter formed / released by the forces exerted on the surrounding rock during the blast;
- Water vapour;
- Carbon Dioxide;
- Carbon Monoxide; and
- Oxides of Nitrogen (NOx)

**PPE (Personal Protective Equipment)** - Items of clothing or devices worn to protect an individual from the actual or potential risks to health or safety arising from an activity or process.

**Pre-Blast Meeting** – A meeting generally conducted at the edge of the delineated shot, prior to the shot being fired but allowing sufficient time for all support personnel to get into position by the appointed time. The meeting must include the following personnel: -

- Shotfirer;
- Blast Controller;
- Sweepers
- Blast Guards
- Other personnel relevant to the blast (e.g. Technical Services Representative, Open Cut Examiner or similar relevant position).

A scaled plan/map shall be provided and the topics for discussion will include:

- Blast notifications
- Blast Guard positions, Sweeper areas and Shotfirer position;
- Exclusion zones: Equipment, Personnel and Fume;
- Production and ancillary equipment locations;
- Personnel locations, including the location of all personnel who may be adversely affected by the blast e.g. maintenance personnel;
- Any exceptional circumstances related to the blast; and
- Weather conditions e.g. wind speed/ direction, cloud cover.

**Pre-Shift Meeting** – A meeting conducted on a mine site prior to or at the beginning of each shift where relevant information is communicated to the general mining personnel such as road reports, mining



activities, blasting activities, sleeping shots, new hazards, changes to procedures, etc.

**Protected works** - The two classes of protected works are as follows: -

- (a) Class A: Public street, road or thoroughfare, railway, navigable waterway, dock, wharf, pier or jetty, marketplace, public recreation and sports ground or other open place where the public is accustomed to assemble, open place of work in another occupancy, river-wall, seawall, reservoir, water main (above ground), radio or television transmitter, main electrical substation, private road which is a principal means of access to a church, chapel, college, school, hospital or factory.
- (b) Class B: Dwelling house, public building church, chapel, college, school, hospital, theatre, cinema or other building or structure where the public is accustomed to assemble, shop, factory, warehouse, store, building in which any person is employed in any trade or business, depot for the keeping of flammable or dangerous goods; major dam.

**Shotfirer** – A person who is licensed to use blasting explosives and is responsible for preparing, charging and firing explosives.

**Standard Operating Procedure (SOP) / Standard Work Practice (SWP)** - A written procedure containing an explicit description of how a job is to be performed. The SOP/SWP identifies the precautions required to safely complete the task, and should include: -

- Personal protective equipment (PPE);
- Hazards specific to the job and/or site;
- The level of authority, responsibility and training required to complete the job safely;
- Reporting relationships identified by management, and any other relationships that may interact with other jobs, SOPs, SWPs or work instructions.

**Sweeper** – Industry terminology for a suitable person/s and equipment (suitable vehicle and communications equipment), who ensures the area inside the Blast Exclusion Zone is clear of personnel.

**Unauthorised Persons** – Personnel not associated with the firing of the blast and, within the designated Blast Exclusion Zone once the Blast Controller have closed the roadways and accesses to the designated Blast Exclusion Zone.

**Unauthorised Traffic** – Personnel operating machinery / vehicles not associated with the firing of the blast and, within the designated Blast Exclusion Zone once the Blast Controller have closed the roadways and accesses to the designated Blast Exclusion Zone.



### 3.0 GENERAL REQUIREMENTS

It is the responsibility of all persons involved in the 'Blast Guard' operations to adhere to the company and/or the site-specific Standard Operating Procedure or Standard Work Practice prior to participating in the activity.

It is the responsibility of the site Supervisor to ensure all personnel involved in the Blast Guard operations complete training in, and adhere to, the company and/or the site specific Standard Operating Procedure or Standard Work Practice prior to participating in the activity.

It is the responsibility of all persons involved to use Risk Management principles to assess all hazards and implement any necessary controls for any event that may be undertaken where there is risk of personal injury or equipment damage.

The equipment operators must have the appropriate qualifications and be appointed and authorised by the relevant site personnel to operate any equipment used in this process, unless under training, and then in accordance with the site training procedures.

Prior to the operation of any equipment used in the Blast Guard process, all relevant pre-start inspections have to be completed and recorded for all machinery that shall be used in the operation.

Equipment is not to be operated by any person where it is not safe to do so or where further relevant training is required by the person.

#### 3.1 PPE and Special Equipment for the Task

The personal protective equipment required for the task will be as follows (as a minimum) with all equipment being in accordance with the blasting company and/or the mine site requirements: -

- Approved Hi Visibility Clothing, Safety Footwear, Eye Protection and Hand Protection

The special equipment required for the task may include the following items:

- Blast Exclusion Zone plan (including a blasting area specific map);
- Mine site compliant vehicle;
- Suitable 2-way radio communication, including site compliant and working two-way radios;
- Approved roadway closure devices (portable signage, vehicle signage, fixed signage, witches' hats);
- Blast guard position markers;
- Global Positioning System unit;
- Traffic Controllers Licence (if required for public road closures);
- Video cameras; Drones and
- Fume monitors.



### 3.2 Selection of Personnel to be a Blast Guard or Sweeper

Personnel selected to be a Blast Guard or Sweeper must have completed all of the relevant site-based training which will be associated with this task. Factors which also need to be considered when selecting personnel to be Blast Guards or Sweepers may include: -

- Suitable literacy and numeracy skills for the task (including an agreed common language to be used during all communication between the Blast Controller, Blast Guards, Sweepers and the Shotfirer);
- Equipment operation competencies;
- Site specific skills and knowledge;
- Physical capability;
- Availability;
- Other competencies or training undertaken;
- Existing responsibilities and accountabilities.

Because Blast Guards and Sweepers may have no direct contact with the explosives or the explosives handling process, the legislative security requirements that apply to the member of the blast crew may not extend to persons fulfilling the Blast Guard role.

### 3.3 Required Competencies and Training

Any person involved in this task must have completed the appropriate company and/or site requirements for the following: -

- Induction program for all employees (generic and site based, as applicable);
- Appropriate vehicle competencies in relation to the vehicles being utilised in Blast Guard duties;
- Appropriate training package for Blast Guarding, including both a theory and practical component by the company and / or mine site;
- A mine site familiarisation tour;
- Emergency response and evacuation procedures;
- Appropriate skills training and licensing of employees as required for operating specialized equipment, or conducting specialized activities e.g. traffic controller; Shotfirer, Blast Controller;
- A regular review and renewal of training and licensing requirements  
(as required by legislation or site requirements);
- Site specific personal protective equipment (PPE) requirements and special / task specific requirements, including training in the proper use of and care of the equipment; and



- Demonstrated competence in relation to agreed radio protocols.

It is recommended that each site, under their Blast Management Plan (refer AS2187.2 – 2006), maintain a register/training records of personnel who are deemed competent and available to perform the role of a: -

- Blast Guard;
- Blast Sweeper and
- Blast Controller.

Such a register/training records should include specific information including: -

- Name;
- Site role;
- Crew / shift;
- Date training completed;
- Date refresher training required; and
- Competencies e.g. Guard, sweeper

### 3.4 Records

The following records need to be maintained:

- Personal Risk Management tools;
- Shot Risk assessment;
- Blast Exclusion Zone map;
- Blast control ancillary information; and
- Blast Guard/Sweeper/Blast Controller Register.



## 4.0 RISK ASSESSMENT

A formal risk assessment should be completed for each blast, identifying the hazards and controls that may be presented by the individual shot at each stage, including the extent of the Blast Exclusion Zone during the firing sequence.

Any risk assessment must be approved and signed by all of the relevant parties involved in the blasting process prior to the blasting process being undertaken.

Factors that should be considered during the risk assessment may include (but not be limited to) the following: -

- The type of shot (cast, stand-up, inter-burden, coal parting, etc.);
- Aim of the shot (maximum fragmentation, maximum heave, etc.);
- The ground type (hardness/bedding planes);
- Known geological abnormalities within the blast design area;
- Burden and spacing (including face row design);
- Average bench height;
- Vertical location of the bench;
- Average blast hole load;
- Any hole slumping, failing to achieve column height at design load, or over loaded;
- The designed powder factor;
- The actual powder factor;
- Timing and effects;
- Blast hole condition e.g. wet, damp, dynamic water;
- Historical records of flyrock and fume events;
- Access to and from the proposed Blast Exclusion Zone;
- The location of equipment and personnel during the blast;
- The location of protected works and/or associated works;
- The location of external infrastructure potentially affected by the blasting activities;
- The formation and management of any blast fume;
- Radio communication 'black spots';
- The expected weather conditions.



## 5.0 BLASTING NOTIFICATION

The site supervisor responsible for the blasting site activities will notify all persons on a mine site, 24 hours prior to the scheduled blasting time.

The Operational Superintendents and other department heads will ensure the blasting information has been passed on to all personnel under their direct control (including sub-contractors) using the site Pre-shift Meetings and other relevant forms of communication such as e-mail.

All blasting notification shall be presented in a format which includes an agreed or common language used for all site personnel.

Notification may include relevant external parties to the mine site within close proximity of the blasting area (e.g rural lease/land holders). Notification of these parties may include telephone communications, emails and/or face to face meetings.

The site Blast Boards will be updated at least the day before the shift start on the day of firing. The site Blast Boards should be positioned to ensure that all personnel entering the mine site and/or relevant sections of the mine site, where blasting activities are forecast, have direct visual information relating to the blasting schedule.

The use of flashing lights to identify the 'active' nature of the Blast Board and positioning of the Blast Boards at pre-shift meeting rooms, 'T' intersections or a 'Stop' sign/security gate, preceding entry to the mine site and/or relevant sections of the mine site, where blasting activities are forecast, are recommended where possible.

The Technical Services personnel associated with the blast will provide a scaled plan or map to be presented at the pre-blast meeting.

The Blast Plan and the scaled plan or map should provide the following information: -

- a) A clear view plan of the shot including;
  - the blast identification number
  - scheduled time and date of firing
  - the Blast Exclusion Zones for all equipment, personnel and fume.
  - the firing position (outside the equipment exclusion zone but if within the personnel exclusion zone what controls will be utilised e.g. barrier type)
  - ancillary information relating to the blast e.g. wind direction/speed;
- b) The nominated Blast Exclusion Zones (equipment, personnel and fume);
- c) All access roads and pathways through the designated Blast Exclusion Zone;



- d) The location of the required Blast Guards and their respective areas of control;
- e) The nominated Shotfirer and Blast Controller;
- f) The approval and sign off from the blast design engineer and other relevant site / blast personnel (e.g. Open Cut Examiner, Drill and Blast Supervisor, Shotfirer, Blast Controller, etc.);
- g) A list of the names of the individual Blast Guards and Sweepers;
- h) A script of the agreed radio procedures and responses;
- i) A table to record any abnormalities exposed during the procedure.
- j) The location of any structure or mobile equipment that will be within the personnel exclusion zone.

The blasting schedule will be provided to the designated mine personnel (e.g. Open Cut Examiner) and details such as blasting inspections (sleeping shots and reload areas) shall be entered into the relevant mine reports where the information can be communicated to the general mining personnel at the morning pre-shift meetings.

The communications of blasting activities to the general mining personnel on the mine site should include blast identification, the blast type, the location, Blast Exclusion Zone distances and the firing times.

Additional forms of blasting notification such as: -

- A site-specific blasting hotline (e.g. 1300 xxx xxx) which could be a recorded message, providing the site-specific forecast blast firing times for all relevant persons;
- A general radio announcement made each day at a nominal time to indicate the blasting requirements of the day.

During the day of the shot, the Shotfirer shall review the site Blast Exclusion Zone plan in conjunction with the other relevant personnel (Technical Services Representative, Blast Controller, Open Cut Examiner) regarding the following: -

- Blast Guard positions;
- Sweep areas;
- Production and ancillary equipment locations;
- Personnel locations, including the location of maintenance personnel;
- Any exceptional circumstances related to the blast.
- The location of any structure or mobile equipment that will be within the personnel exclusion zone.
- Fume management zone



The Blast Controller shall confirm that the appropriate people have been notified in relation to machinery and people to be removed from the exclusion zone. (e.g. Pit Foreman, Maintenance Foreman, Pump Crew Foreman, Dragline Operator).

This should be done as early as possible prior to the shot being tied in and again the information shall be conveyed to all at the Blast Guard meeting.

If it has been determined that the blast exclusion area encompasses a public roadway and/or rail line, it will be confirmed at the pre-blast meeting that the relevant authorities have been notified and appropriate controls are in place.



## 6.0 PUBLIC ROADWAY / RAILWAY CLOSURES/AIR TRAFFIC

The requirements for a person to perform the Blast Guard role and close a public roadway may include the provision of a 'Traffic Controller' qualification, as per the local authority requirements. This should be investigated prior to any public road closure and the nominated persons to perform the role under such circumstances are to be appropriately equipped and qualified for the role.

It should be noted that approval for any diversion of air traffic or closure of any air strip, rail line or public roadway, is required from the appropriate controlling authority body, and is subject to the application and notification of blasting activities within these areas.

The timeframes and required information for such applications will be as per the relevant controlling authority specifications and may vary from state to state.

The Blast Controller is to ensure that the Blast Guards who are responsible for any public roadway closure, have the appropriate signage positioned on the boundaries of the Blast Exclusion Zone in these areas at least 30 minutes prior to the proposed firing time.



## 7.0 THE BLAST GUARDING PROCESS

The person assuming the role of the 'Blast Controller' will be responsible for the logistical elements of the blast in terms of: -

- a) Prior to the Blast Guard meeting, ensuring that adequate resources are available to provision the Blast Exclusion Zone in terms of: -
  - A map is provided to all personnel (blast guards, sweeper, supervisors) involved in managing the Blast Exclusion Zone. The map will detail all blast guard locations, sweep areas, shotfirer location and fume fall back locations.
  - The correct numbers of competent personnel required to manage the Blast Exclusion Zone are available and have been advised of the blast guard meeting time and location;
  - The required numbers of suitable vehicles and radios;
  - Visual indicators associated with each blast guard location;
  - All required internal and external notifications have been made.
- b) Ensuring that the designated Blast Exclusion Zone is clear of all personnel and equipment, in accordance with the specification of the blast design, and in accordance with the nominated site timeframes, prior to the firing of any blast, by communication with the relevant mine site personnel supervising non-blast related activities within the designated Blast Exclusion Zone;
- c) Establishing the security of the Blast Exclusion Zone perimeter, including the positioning and monitoring (visually and by radio contact) of the blast guards; and
- d) Conducting a safety sweep of the designated Blast Exclusion Zone once the blast guards have confirmed all access points have been blocked. The sweep process ensures the Blast Exclusion Zone is clear of all personnel and equipment prior to the firing.

Each person designated as a Blast Guard will have two main roles: -

- a) To create a physical barrier at a defined access point to a blast area to ensure no persons can enter the Blast Exclusion Zone during the firing process;
- b) To immediately communicate any breach of the Blast Exclusion Zone to the Shotfirer and/or the Blast Controller.

Each person designated as a Sweeper will have two main roles: -

- a) To drive through their nominated area/s to ensure the Blast Exclusion Zone is free of personnel;  
To fly a drone through their nominated area/s to ensure the Blast Exclusion Zone is free of personnel
- b) To immediately communicate any breach of the Blast Exclusion Zone to the Shotfirer and/or the Blast Controller.



A sign or barricade is NOT sufficient to ensure that unauthorised persons are NOT within the area of danger prior to blast firing process.

Physical checks and guards are a mandatory part of any blast clearance process.

The obligation of Blast Guards and Sweeper/s is to work under the direct instructions of the designated Blast Controller and no other person for the duration of the blast guarding duties.

The Blast Guards will proceed to the designated Blast Guard barricade points and wait for instruction from the Blast Controller to secure the Blast Exclusion Zone access point.

Once all the Blast Guards are in position at the nominated barricade point, the Blast Controller will direct all access to the Blast Exclusion Zones is to be closed by a physical barrier, e.g. by parking their vehicle at a 90° angle to the Blast Exclusion Zone access

Once the Blast Guards have confirmed their locations are blocked and secure the Blast Controller will instruct the Sweeper/s to commence the clearance run.

The clearance inspection may be performed with a drone if there are no structures or mobile equipment inside the personnel exclusion zone.

During the sweep/clearance run the Sweeper/s may need to get out of their vehicle as required, to check areas that are not accessible by a vehicle or where machines have been shut down for mechanical repairs, to ensure all persons are evacuated (e.g. crib huts, amenities buildings, temporary buildings, dragline lay down pads).

Once the sweep is completed, the Sweeper/s will then return to the Blast Guard location nominated at the Blast Guard meeting.

The Sweeper/s must then report the results of the inspection to the Blast Controller via the 2-way radio and receive confirmation of the message from the Blast Controller.

The Blast Controller will, after receiving confirmation from the Blast Guards and Sweepers that the Blast Exclusion Zone is secured confirm the area is secure with the Shotfirer.

Under NO circumstances will the Blast Guards or Sweepers leave their position until the Shotfirer has given the "ALL CLEAR" and confirmed with each Blast Guard via the 2-way radio system that their duties have been completed.

In the event that a Blast Guard barricade has been breached or the Blast Guard observes personnel within the exclusion area, the blasting process MUST immediately be stopped by notifying the Shotfirer/Blast Controller via the 2-way radio.

The Blast Guard will immediately call on the designated 2 Way Radio channel "DO NOT FIRE, Guard (guard number)" or similar agreed call, twice and wait for a response from the Shotfirer.

If there is no response from the Shotfirer / Blast Controller within 2-3 seconds the Blast Guard is to make the call again. The Blast Guard will continue to broadcast the radio alert of the unauthorised access,



until receiving a suitable response from the Blast Controller or Shotfirer.

The Shotfirer/Blast Controller will acknowledge the radio call from the Blast Guard and then: -

- Immediately abort the firing procedure and, disconnect and secure, the explosives initiating (firing) apparatus;
- Confirm with the Blast Guard the details of any reported breach of the Blast Exclusion Zone.
- Communicate to all Blast Guards to hold their current positions;
- Release the radio silence;
- Document the details of the reported breach of the Blast Exclusion Zone (blast guard number, time, area, vehicle / person identification, etc.);
- Investigate the reported breach of the Blast Exclusion Zone;
- Consider what corrective actions are to be taken (e.g. restart the firing procedure / reschedule the firing of the blast).

If there is no response from the Shotfirer/Blast Controller to the initial radio alert from the Blast Guard, a relay radio message may be required to be passed to the Shotfirer/Blast Controller from another Blast Guard, or relevant site personnel who have heard the radio alert call.

The Blast Guard who has witnessed/reported the unauthorised access within the closed Blast Exclusion Zone shall not leave the designated position, to follow or remove any unauthorised personnel, under any circumstances.

Under these conditions the firing of the blast will be delayed, and the designated Blast Controller will investigate all reports of unauthorised access within any closed Blast Exclusion Zone, before resuming the blast firing sequence.

Following investigation, the Blast Controller will provide a report of any unauthorised access to a blast exclusion zone to the site supervisor.



## 8.0 PRE-BLAST MEETING

At an agreed time (e.g. 60 minutes) prior to the blast firing time the nominated Blast Guards will meet at the blast location.

At this time, prior to conducting the Blast Guard Meeting, a general radio announcement will be made to all mine personnel indicating the firing of the blast at e.g. 13:00hrs. This notification should include the blast identification, the blast location and the type of blast.

Confirmation of the blast notification from the production superintendent and Open Cut Examiner, where applicable, is required.

The pre-blast meeting must involve the following personnel:

- Shotfirer;
- Blast Controller;
- Sweepers;
- Blast Guards; and
- Other personnel relevant to the blast.

The purpose of this meeting is to discuss:

- a) The Blast Area Exclusion Zone plan (equipment, personnel and fume);
- b) The designated 2-way radio channel to be used for the blast location;
- c) The firing location;
- d) The issued Blast Guard location information sheets which will indicate: -
  - the position of Blast Guards;
  - the Blast Guard positions in relation to any change in the original blast design parameters or identified hazards;
  - the relevant Blast Guard numbers;
  - the Sweepers and assigned areas;
  - the process for the clearance of the blast area, including the positioning of machines and any ancillary equipment; and
  - any exceptional circumstances relating to the blast.

Prior to completion of the meeting, all Blast Guards and Sweepers shall verify their understanding of their position and area requirements.

All personnel involved with the blast should conduct a radio check to ensure the allocated radio is on the correct channel and operable before dispersing to their nominated position.



At a time approximately 30 minutes prior to the firing of the blast, the Blast Controller will confirm with the Blast Guards and Sweepers via the 2-way radio that they are in their allocated positions. Confirmation from each Blast Guard and Sweeper is required.

## 9.0 ESTABLISHING THE BLAST GUARD POSITIONS

Blast Guard positions are to be identified prior to the commencement of loading the shot. The Blast Guard location markers must be positioned prior to the Blast Guard meeting.

The Blast Guard positions can be identified by a site-specific process and marker (e.g. coloured witches' hat) with the distance to the shot being verified using the preferred method of a Global Positioning System unit analysis. This will provide personnel with a clear Blast Exclusion Zone marker in the event of having to close the Blast Exclusion Zone during a thunderstorm or an emergency event.

It is to be noted however, that hazards identified during the loading of the blast (e.g. overloaded blast holes, insufficient face row burden, geological abnormalities) or a change to the blast parameters (e.g. to meet a revised mining schedule, driven by a significant weather event) may then require the original Blast Guard positions to be reviewed and changed, in accordance with the requirements or conditions of the blast design.

Prior to the shot being fired, the Blast Guards and Sweepers must be in position at an agreed time (e.g. 30 minutes) before the blast. This may vary depending on the clearance area and will be site specific.

Once asked to close access to the Blast Exclusion Zones, the Blast Guard vehicle is to be parked in a position that blocks the access to the exclusion area and is clearly visible to all oncoming traffic.

Each designated Blast Guard vehicle will have a working flashing light activated (hazard lights may be used as well) and have 2-way radio communications (either hand held or vehicle mounted) with the nominated Blast Controller.

In the event of the designated Blast Guard position being located in a radio 'black spot', the position may need to be relocated to an alternative position where clear radio communications can be clearly established prior to the firing of the shot. This action will be completed through consultation and with the approval of the Blast Controller.

The Blast Guard position will allow clear vision of the position access along roadways and the surrounding area and shall not be located in a position that can cause confusion or place the blast guard in danger from moving traffic (e.g. on corners, directly on intersections, etc.).

Blast Guards must remain with the vehicle and ensure there is ready 2-way radio communications during the Blast Guarding process.

Once in position, no unauthorised traffic or personnel will be permitted to pass the Blast Guard location, unless evacuating the exclusion area, or in an event of an emergency.

The Shotfirer/Blast Controller must be notified immediately via the 2-way radio of any emergency condition.

If a public roadway is to be closed, all vehicle traffic will be stopped at the Blast Guard position and a clearance run of the section of roadway must be completed between the Blast Guard positions prior to the firing of the shot.

In most cases involving railways the rail authority will manage the closure, clearance and re-opening of



the rail corridor.

The Blast Controller must then be notified that the public roadway and/or rail line are all clear within the blast exclusion area.

### **9.1 Blast Guarding During a Thunderstorm**

In the event of a thunderstorm approaching a loaded or partially loaded shot, all personnel working within the designated Blast Exclusion Zone must be evacuated, with blast guards posted to the relevant positions to ensure that the effects of any potential unplanned initiation caused by a lightning strike are minimised.

In this case, personnel may be directed to close the roadways and access paths to the designated Blast Exclusion Zone for the duration of the storm at the discretion of the site management team.

In such cases, the location of blast guards must consider risks from lightning and/or flooding.

### **9.2 Blast Guarding During an Emergency**

In the event of an emergency situation on a loaded or partially loaded shot, all personnel working within the designated Blast Exclusion Zone must be evacuated, with blast guards posted to the relevant positions to ensure that the effects of any potential unplanned initiation caused by fire and / or any other potential ignition source are minimised.

In this case, personnel may be directed to close the roadways and access paths to the designated Blast Exclusion Zone for the duration of the emergency event at the discretion of the site management team.

In accordance with the site Emergency Procedures and/or the explosives company Emergency Procedures the Blast Exclusion Zone may be altered from the original plan, with due consideration given to the risk potential of the situation.

In this event the parameters of the Blast Exclusion Zone will be communicated to all personnel by a member of the site management team or a delegated authority.



## 10. CLEARING THE BLAST EXCLUSION ZONE

The Blast Controller will instruct the Sweepers to conduct a safety sweep or clearance of the Blast Exclusion Zone once all of the Blast Guards have confirmed that they are in the correct location and access is blocked and secure.

Prior to conducting the sweep of the Blast Exclusion Zone, the Sweepers will familiarise themselves with the operations and work areas currently in use within the designated Blast Exclusion Zone.

During the sweep of the Blast Exclusion Zone the Sweepers will verify the position and conformity of the Blast Guard position during the sweep.

The Sweepers must complete a full clearance inspection of the designated Blast Exclusion Zone to ensure the following: -

- a) All personnel have been removed from the designated Blast Exclusion Zone;
- b) Where possible, all equipment has been removed from the designated Blast Exclusion Zone. If equipment remains within the Blast Exclusion Zone acceptance of the potential for damage must be noted on the blast JSA;
- c) As a minimum requirement all equipment that cannot be removed must: -
  - Stop operation and shutdown;
  - Be appropriately isolated;
  - Be secured against the effects of the blast.

The sweep inspection may be performed using a drone but only if there are no structures and mobile equipment within the personnel exclusion zone.

During the inspection, the Sweepers may be required to leave the vehicle to check any areas that are not accessible by vehicle, to ensure that all persons have been evacuated (e.g.: - crib huts, amenities buildings, temporary buildings).

In this case the Sweeper must remain in direct radio contact with the Blast Controller by the use of a hand held 2-way radio.

In areas such as crib huts, amenities, temporary buildings, banded work areas and parked machinery where personnel may be working remotely or out of radio contact, the Sweeper may use a device, such as an audible alarm upon entry to the area, to alert personnel to their presence and await any response.

On completion of the clearance inspection, the Sweeper must return to the Blast Guard location nominated during the Blast Guard meeting and report the clearance run has been completed and No Personnel are within the Blast Exclusion Zone.

When the Blast Controller has received confirmation from the Blast Guards and Sweepers the Blast Exclusion Zone is clear: -



- The Blast Controller will hand the control of the Blast Exclusion Zone over to the Shotfirer who will commence the firing sequence, beginning with a warning (e.g. 10 minute) to all site personnel in accordance with the company and/or mine site blast firing procedures. During this time the blast initiating mechanisms will be installed and prepared for firing.
- The Shotfirer will then commence the firing sequence with a 2-minute warning to all site personnel. This will include a final check of the area by radio with each Blast Guard.



## 11.0 FIRING THE SHOT

The Blast Controller will advise the Shotfirer that the Blast Guards and Sweepers are in position and the Blast Exclusion Zone is secure and clear of unauthorised personnel and equipment.

The Shotfirer will raise any concerns regarding the blast guards and/or the clearance procedure before accepting the control of the blast and designated blast area.

The Shotfirer will confirm the Blast Exclusion Zone is blocked and secure and accepts control of the blast and designated blast area.

The Shotfirer will call for radio silence at the 2-minute mark from the firing time; silence shall be maintained unless an emergency situation arises.

By using the agreed radio protocol to confirm the security of the Blast Exclusion Zone and announce the 2-minute warning, the Shotfirer has accepted control of the blast and the designated Blast Exclusion Zone.

The Shotfirer will call a 2-minute warning prior to firing.

The Shotfirer will broadcast a 15 second warning alarm over the 2-way radio system prior to firing.

The Shotfirer will complete the site firing procedure in accordance with the site accepted practices and fire the blast.

*NOTE:-*

*If the Blast Guard position or exclusion area is breached at any stage in this process, the Shotfirer must be immediately notified via the 2-way radio to stop the firing sequence by the Blast Guard.*

*The Blast Guard will immediately call on the designated 2-way radio channel "DO NOT FIRE, Guard (guard number)," or similar agreed call, twice and wait for a response from the Shotfirer, and will continue to do so until there is a response from the Shotfirer.*

### 11.1 The Management of 'Post-Blast Fume'

Sometimes large clouds of 'Post-Blast Fume' are generated after the initiation of ammonium nitrate-based explosives, which may be yellowish through to a red/brown colour. The cloud will generally be composed of the following materials:

- Dust and other soil / rock particulate matter formed / released by the forces exerted on the surrounding rock during the blast;
- Water vapour;
- Carbon Dioxide;
- Carbon Monoxide; and
- Oxides of Nitrogen (NO<sub>x</sub>)



Oxides of Nitrogen (NO<sub>x</sub>) are a mixture of gases that are composed of nitrogen and oxygen. Two of these gases are nitrogen dioxide and nitric oxide, which are known to have toxic effects.

Any person who experiences the subsequent symptoms following exposure (low level exposure symptoms only) to 'Post-Blast Fume' must seek immediate medical treatment. Such symptoms include:

- Irritation to the eyes, nose, throat and lungs;
- Coughing and shortness of breath;
- Tiredness and nausea;
- A build-up of fluid in the lungs (possibly taking 1 -2 days).

For more information on 'Post-Blast Fume' reference should be made to the AEISG Code 'Prevention and Management of Blast Generated NO<sub>x</sub> Gases from Surface Blasting'.

The following personnel have been identified as those generally at the greatest risk of exposure to Oxides of Nitrogen (NO<sub>x</sub>) during the explosives detonation process: -

- a) Shotfirers and Support Personnel may be exposed to the Oxides of Nitrogen (NO<sub>x</sub>) gases during the post blast period by moving back into the general blast area prior to the dispersion of the gasses;
- b) Shotfirers and Support Personnel may be exposed to the Oxides of Nitrogen (NO<sub>x</sub>) gases during the post detonation inspection of the blast area as the dispersion of the gasses can be very localised and continue to leak from under the ground for some time after the initial blast;
- c) Shotfirers and Support Personnel may also be exposed to the fume cloud during the blast guarding process;
- d) General mining personnel who may be exposed to the production of the NO<sub>x</sub> gases during the dispersion of the 'Post-Blast Fume' cloud across a site;
- e) Personnel that gather at areas such as blast guard positions and crib huts, close to the edge of the Blast Exclusion Zone.

Such personnel need to be monitored during the 'Post-Blast Fume' dispersion to ensure personnel in any exposed positions are advised and take appropriate actions.

As a part of the Blast Guard procedure, the formation and direction of all 'Post-Blast Fume' clouds must be monitored by the Shotfirer/Blast Controller.

Blast Guards may also report the direction of any 'Post-Blast Fume' clouds if they consider their position to be at risk of exposure to the cloud.

In the event of Post-Blast Fume moving away from the blast towards a known Blast Guard location, the Shotfirer/Blast Controller may direct the personnel at that particular location to: -



- a) Withdraw from their present location to an alternative position along the roadway or access pathway;
- b) Remain in side any vehicles or crib huts with the windows closed and the air conditioner on re-cycle.

While it is unlikely that exposure to these gasses will result in a fatality due to the concentration of the gasses in an outdoor/well ventilated mining area, the Oxides of Nitrogen (NO<sub>x</sub>) must be recognised as a potential threat and managed accordingly.



## 12.0 BLAST FIRED

Once the blast has been fired, the Shotfirer will lift the radio silence and state: “All Blast Guards are to remain in their position until the “ALL CLEAR” is given”.

The Blast Controller will visually monitor the effects of the blast, before allowing the Shotfirer to return to the blast site, and make an assessment as to the potential risks associated with any post-blast inspection.

The assessment shall consider the minimum waiting time prior to conducting the post-blast inspection, and include (but not limited to) consideration of the following factors:

The recovery and securing of all types of initiating devices from firing lines;

- If there is a need for more than one person to return to the shot for the inspection;
- Whether fume dispersal has occurred;
- Whether dust dispersal/settlement has occurred;
- The identification of any apparently unstable ground;
- The safety and suitability of access and egress;
- Aspects of the blast that may indicate that not all of the charges have been initiated;
- In the case of a misfire, or a suspected misfire, whether the minimum waiting time has been observed;
- The availability of a competent person to inspect for safety, ground or material that did not move as intended;

Who may enter the exclusion zone prior to conducting the post-blast inspection.

When advised by the Blast Controller, the Shotfirer will then inspect the blast and may confirm the “ALL CLEAR” after giving due consideration to: -

- Identification of any misfire and/or the associated corrective action required to make the area safe;
- Procedures to be adopted, if the inspection reveals that the “ALL CLEAR” cannot be given;
- Continuous inspection procedures during the approach to the post blast site that might identify unusual or abnormal results indicating possible hazards;
- Whether there is a need to wash down/or scale exposed surfaces;

The Shotfirer may then communicate:

- That a misfire or other problem has been identified and the “ALL CLEAR” cannot be given and that further action is required, or
- That the “ALL CLEAR” has been given and that normal operation may recommence.



Where the “ALL CLEAR” has been given by the Shotfirer, the Blast Controller will then release the Blast Guards in numerical order. (Blast Guards must reply to the message).

Blast Guards will acknowledge the “ALL CLEAR” message.

The rail authority personnel will generally control the rail line clearance and re-opening in accordance with the communication from the Shotfirer/Blast Controller.

The Blast Guards performing the traffic control operations on any public roadway are to remain in place at the designated public roadway positions until such time as:

- a) The “ALL CLEAR” is given by the Shotfirer; and
- b) Before traffic flow resumes, the section of the roadway between the Blast Guard positions must be inspected for blast debris with the removal of any material that may have landed on the roadway.
- c) This inspection is performed by the nominated third person who is in position with the Blast Guard prior and during the blast.
- d) Following the inspection of the public roadway, the Shotfirer may allow the resumption of traffic flow on the public roadway during the post blast inspection timeframe at their discretion, taking into consideration all due circumstances, however the Blast Guards will remain in position until the ‘All Clear’ has been given and confirmed.

NOTE: Until the “ALL CLEAR” signal is given, no traffic or personnel are permitted to gain access to the Blast Exclusion Zone (This is to allow for the treatment of any misfires found with the possibility of re-firing at the time.).



## 13.0 MISFIRE MANAGEMENT

In the event of a misfire being declared by the Shotfirer, all Blast Guards are to remain in position and ensure the Blast Exclusion Zone is maintained.

A misfire may include: -

- a) The total failure of the blast to initiate as designed;
- b) The failure of a section of the blast to initiate as designed; or
- c) The failure of whole or partial individual blast holes to initiate as designed.

Misfires may be identified during: -

- a) The firing procedure;
- b) The post firing inspection; or
- c) The mining excavation process.

When a misfire has been identified during the post blast inspection the Blast Controller will regain control of the Blast Exclusion Zone perimeter and all communications.

The Shotfirer will control the mechanics of the misfire and keep the Blast Controller informed in regards to action that result from the misfire.

If a misfire which has been identified during the initial firing sequence, or during the post blast inspection, can be safely re-fired while the Blast Guards are in position, the suitable notifications and preparations are to be implemented and re-firing conducted as soon as possible. However, the Blast Exclusion Zone parameters may have to be extended to a greater distance at the discretion of the Shotfirer.

All instructions issued by the Shotfirer during the re-firing of a misfire, must be complied with and confirmed by each Blast Guard. This may include a second safety sweep (clearance) of the Blast Exclusion Zone by the Sweepers if it is deemed required prior to the re-firing of the misfire.

Once the misfire is ready to be re-fired, the normal firing sequence will commence from the 2-minute warning and Blast Guard checks.

Misfires scheduled to be fired after the initial firing schedule, must follow the firing process as per any normal blasting activity, and include a risk assessment which would include the number and placement of suitable Blast Guards required for the blast.

## APPENDIX A: AUSTRALIAN STANDARDS REFERENCED

AS2187.0 - 1998 Explosives – Storage, transport and use – Terminology.

AS2187.1 - 1998 Explosives – Storage, transport and use. Part 1 – Storage.

AS2187.2 – 2006 Explosives – Storage, transport and use. Part 2 – Use of Explosives.

# APPENDIX B: EXAMPLE OF THE BLAST CONTROLLER CHECKLIST

BLAST CONTROLLER CHECKLIST								
Shot ID:	Date:	Time of blast guard meeting:			AM / PM			
		Blast Guard Meeting Location			AM / PM			
		Blast Guards Despatched:			AM / PM			
		Time of Firing:			AM / PM			
Blast guards								
Number	Name	Distance	Position	Call sign (if applicable)	Attended Meeting	On Standby	1 <sup>st</sup> call	2 <sup>nd</sup> call
1					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
4					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
5					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
6					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Sweepers								
Number	Name	Sweep Area		Call sign (if applicable)	Attended Meeting	On Standby	1 <sup>st</sup> call	2 <sup>nd</sup> call
1					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
2					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
3					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Notifications								
To;					Email Notification	Verbal	Evacuation required	
Issued to Mine Manager or Delegate 24hrs prior to blast					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Mine Manager or Delegate issued notification for day of blast to all on					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
All personnel on site notified 24 hours prior to blast at pre-start					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Notification of near neighbours prior to blast if required					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Administration Office					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Workshop					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Stores					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Processing Plant					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Exploration Office					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Other- Contact Details (as required) -					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	
Equipment / Personnel Evacuation Required Checklist								
Location	Distance (m)	Evacuation Required Yes	Cleared and Checked		N/A			
Administration building		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>			
Mine Muster Building and Change rooms		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>			
Assay Laboratory		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>			
Processing Plant external areas		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>			
ROM Pad		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>			
		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>			
		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>			
		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>			
Shot Firer/Blast Controller Confirmations								
Blast Controller confirms the exclusion zone is clear and ready to fire								<input type="checkbox"/>
Shot Firer confirms clearance and connects firing line								<input type="checkbox"/>
Shot Firer Calls 2 minutes to firing and sounds siren for 30 seconds								<input type="checkbox"/>
Shot Firer calls 10 seconds to firing								<input type="checkbox"/>
Shot Firer calls 1 second to Firing and then Firing								<input type="checkbox"/>
Shot Firer calls all Blast Guards to hold position until shot clearance completed								<input type="checkbox"/>
Shot Firer declares the shot all clear								<input type="checkbox"/>
Blast Controller stands-down the Blast Guards and releases the blast exclusion zone								<input type="checkbox"/>

Hole conditions prior to blast			Exclusion Zones	
	Yes	No	Distance in metres	
Rain during or after loading?	<input type="checkbox"/>	<input type="checkbox"/>	Personnel:	
Holes had water in them?	<input type="checkbox"/>	<input type="checkbox"/>	Equipment:	
Damp sides?	<input type="checkbox"/>	<input type="checkbox"/>	Fume:	
Were the holes dewatered?	<input type="checkbox"/>	<input type="checkbox"/>	Fume management zone required? <input type="checkbox"/> Yes <input type="checkbox"/> No	
Rain during/after loaded?	<input type="checkbox"/>	<input type="checkbox"/>	Comments:	
Any slumping holes?	<input type="checkbox"/>	<input type="checkbox"/>		
Loaded to design?	<input type="checkbox"/>	<input type="checkbox"/>		
Hole-by-hole data captured?	<input type="checkbox"/>	<input type="checkbox"/>		

Weather Conditions				
Weather prior to firing (tick applicable)		Sunny	Cloudy	Temperature (°C)
	Calm	<input type="checkbox"/>	<input type="checkbox"/>	30+ <input type="checkbox"/>
	Minimal wind	<input type="checkbox"/>	<input type="checkbox"/>	20-30 <input type="checkbox"/>
	Windy	<input type="checkbox"/>	<input type="checkbox"/>	Below 20 <input type="checkbox"/>

Monitor Locations						
<input type="checkbox"/> Applicable			<input type="checkbox"/> Not applicable			
Monitor No.						
Northing						
Easting						

Post-firing fume conditions						NOx Reading in PPM (if applicable)
Fume rating	0	1	2	3	4	5
	<input type="checkbox"/>					

Blast confinement in fume	<input type="checkbox"/> Fully buffered	<input type="checkbox"/> Half buffered	<input type="checkbox"/> Free face	<input type="checkbox"/> Box cut		
Type of stemming in fume location	<input type="checkbox"/> Crushed aggregate	<input type="checkbox"/> Drill	<input type="checkbox"/> Coal rejects	<input type="checkbox"/> Sand	<input type="checkbox"/> Gravel	<input type="checkbox"/> Other
Product in fume location	<input type="checkbox"/> ANFO	<input type="checkbox"/> HANFO	<input type="checkbox"/> Pumped	<input type="checkbox"/> Mixture /		
Fume visual after blast	<input type="checkbox"/> Visible instantly		<input type="checkbox"/> Visible in < 5 mins		<input type="checkbox"/> Visible in > 5 mins	
Fume visibility after blast	<input type="checkbox"/> Stayed low after blast		<input type="checkbox"/> Came out of shot	<input type="checkbox"/> Came out through face	<input type="checkbox"/> Directly into the air	
Fume location	<input type="checkbox"/> From initiation point	<input type="checkbox"/> Rear of the blast	<input type="checkbox"/> Middle of the blast	<input type="checkbox"/> Buffered end	<input type="checkbox"/> Corner of blast	

Wind Speed – Travel Time (minutes)			Wind Conditions		
		Distance (km)	Prior to blast		

		1	2	5	10	Wind speed (km/h):
Speed (km/h)	5	12	24	60	120	Wind direction (e.g. NNE):
	10	6	12	30	60	Cloud cover (0 nil to 10 full):
	20	3	6	15	30	Comments:
	40	2	3	8	15	

Sign off			
	Name (in full)	Signature	Date
Blast Controller			
Shotfirer in charge of shot			

## APPENDIX C: EXAMPLE OF THE BLAST CONTROLLER SCRIPT

- Blast Controller: “Copy all mine personnel, there will be a blast at “location” in approximately 30 minutes. Please maintain radio silence until further notice”.
- Blast Controller: “All Blast Guards and Sweepers please call when in position and standing by”.
- Blast Guards and Sweepers: “Copy Blast Controller, Blast Guard number 1 in position and standing by” (call in is in sequential order)
- Blast Controller: “Copy Blast Guard number 1 in position and standing by” (the Blast Controller marks the checklist as each call is confirmed)
- Blast Controller: “Copy Shotfirer the Blast Guards and Sweepers are in position and standing by”
- Shotfirer: “Copy Blast Controller, ready to proceed please secure the exclusion zone”
- Blast Controller: “Copy Shotfirer securing the exclusion zone”
- Blast Controller: “Copy Blast Guards please secure the exclusion zone and acknowledge when secure”
- Blast Guards: “Copy Blast Controller, Blast Guard number 1 in position and area secure” (call in is in sequential order)
- Blast Controller: “Copy Blast Guard number 1 in position and area secure” (the Blast Controller marks the checklist as each call is confirmed)
- Blast Controller: “Copy Sweepers, the exclusion zone is secure please commence clearance runs”
- Sweepers: “Copy Blast Controller, Sweeper number 1 commencing clearance run” (call in is in sequential order)
- Blast Controller: “Copy Sweeper number 1, commencing clearance run” (the Blast Controller marks the checklist as each call is confirmed)
- Sweepers: “Copy Blast Controller, Sweeper number 1 completed clearance run and all personnel clear and I have returned to standby Blast Guard position” (call in is in sequential order)
- Blast Controller: “Copy Sweeper number 1, clearance run complete and area secure of personnel and you have returned to stand by position” (the Blast Controller marks the checklist as each call is confirmed)
- Blast Controller: “Copy Blast Guards, please confirm areas are still secured”
- Blast Guards: “Copy Blast Controller, Blast Guard number 1 in position and area secure” (call in is in sequential order)
- Blast Controller: “Copy Blast Guard number 1, in position and area secure” (the Blast Controller marks the checklist as each call is confirmed)
- Blast Controller: “Copy Shotfirer, the exclusion zone is secure, all Blast Guards and Sweepers are in position”
- Shotfirer: “Copy Blast Controller, exclusion zone secure, connecting lead in line”
- Shotfirer: “Copy all mine personnel, the shot will be fired in 2 minutes, please maintain radio silence”
- Shotfirer: “Copy all mine personnel the shot will fire in 1 minute”
- Shotfirer: “Copy all mine personnel the shot will fire in 10 seconds”
- Shotfirer: “Copy all mine personnel “Firing”
- Shotfirer: “Copy all mine personnel the shot has fired, please hold position until the All Clear is given”
- Shotfirer: “Copy Blast Controller, the shot has been inspected and is All Clear”
- Blast Controller: “Copy Shotfirer, the shot has fired and the All Clear has been given”

- Blast Controller: “Blast Controller to all mine personnel, the blast has fired and the Shotfirer has given the All Clear. Normal operations may recommence.
- Blast Controller: “Copy Blast Guards, the shot has fired and the Shotfirer has given the All Clear”
- Blast Guards: “Copy Blast Controller, Blast Guard number 1 standing down”

## About AEISG

The Australian Explosives Industry Safety Group (AEISG) is an incorporated association of Australian explosives manufacturers and suppliers originally formed in 1994.

Since then, AEISG membership has grown substantially to include most of the Australasian explosives industry.

A full list of all current member organisations can be found on the AEISG website, [www.aeisc.org.au](http://www.aeisc.org.au)

The goal of AEISG is to continuously improve the level of safety and security throughout our industry in the manufacture, transport, storage, handling and use of explosives and related materials across the region.

One of the strategies adopted by AEISG in this regard is to identify areas where improved and consistent standards of operational safety and security need to be applied, and then develop appropriate codes which reflect industry best practice in these areas.

AEISG codes of practice are adopted by members for the benefit of their employees, their customers and the general community. In the interest of promoting safety and security, the codes are freely available on the AEISG website.

